

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ FLASHLIGHT

XPR-5542GMX

NIGHTSTICK
Life Depends on Light™



DUAL-LIGHT™

275-lumen Dual-Light™ mode provides simultaneous **flashlight and floodlight** operation

IP-67
DUST/WATER
PROOF

INTEGRATED
HEAVY-DUTY
MAGNET



Large, textured buttons that are **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



Non-conductive body designed for hazardous environments



Powerful base magnet allows "hands-free" use

400 LUMENS

CERTIFIED



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

DUAL-LIGHT™ FLASHLIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5542GMX - 017398806008

CERTIFICATIONS/MARKINGS

- cULus
- ATEX
- IECEX
- Serialized for personal identification

CASE MATERIAL

- Glass Filled Nylon Polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 400 lumens, 10 hrs runtime
- MEDIUM: 170 lumens, 19 hrs runtime
- LOW: 80 lumens, 41 hrs runtime
- STROBE

FLOODLIGHT

- HIGH: 225 lumens, 11 hrs runtime

DUAL-LIGHT

- 275 lumens, 10 hrs runtime

CANDELA

- HIGH: 11,571

BEAM DISTANCE

- HIGH: 215m

WATER RATING

- IP-67 (dustproof/waterproof)

DROP RATING

- 2m

DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- BARREL DIAMETER: 1.2 in (30 mm)
- BEZEL DIAMETER: 1.6 in (40 mm)
- WEIGHT: 10.9 oz (309 g)

BATTERY







- Integrated li-ion battery (included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Light
- li-ion rechargeable battery
- Snap-in rapid charger
- AC/DC power supplies
- Anti-roll ring
- Instruction manual

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	400 LUMENS	225 LUMENS	275 LUMENS
	10h	11h	10h
	215m		
	11571cd		
	2m		
	1m		

	Bayco Products, Inc. XPR-5542 Wylie, TX 75098
E 467756 INTRINSICALLY SAFE SECURITE INTRINSEQUE	Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS UL listed for use with Bayco Li-Ion Battery Pack 5500-BATT
	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 0 GRP IIC T4 CLASS II ZONE 20 IIC T130°C © II 1 G Ex ia IIC T4 Ga
	Ex ia IIC T4 Ga DEMKO 19 ATEX 1815 IECEX UL 16.0168 -20°C ≤ Tamb ≤ +40°C 3.7V/Cell 5500-BATT UL = 4.75V

CERTIFIED

