



TLR-7® sub

**COMPACT RAIL MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH
GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X RAIL AND GLOCK® 48 RAIL
SUBCOMPACT HANDGUNS**

MARKET

APPLICATIONS: Law Enforcement, Security, Sporting Goods, Consumer

DESCRIPTION: Ultra lightweight & compact, the TLR-7® sub Weapon-Mounted Tactical Light features the latest in LED technology for high lumen operation and provides 1.5 hours of continuous runtime from a single lithium battery. 500 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. Featuring a specialized clamp system for mounting on GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X Rail and GLOCK® 48 Rail.

CASE MATERIAL: Body and Facecap: 6000 Series machined aircraft aluminum with black anodized finish.
Switch housing: Impact and chemical resistant engineered polymer.

DIMENSIONS: Width: 1.16 in (2.95 cm) Height: 1.24 in (3.15 cm) Length: 2.51 in (6.38 cm)

WEIGHT: 2.39 oz (67.8 grams) with battery (included with purchase).

LENS: High temperature, shock mounted, impact resistant Borofloat® glass.

LIGHT SOURCE: LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 500 lumens, 5,000 candela peak beam intensity and 141 m beam distance.
Custom TIR optic produces a concentrated beam with optimum peripheral illumination.
Optimized electronics provide regulated intensity.

ON/OFF: Rear switches left and right of trigger guard provide ambidextrous operation.
Quick press for constant on operation and press and hold for momentary operation.
Double tap either switch within ¼ second activates strobe (if enabled).

RUN TIME: 1.5 continuous hours to the 10% output level.

BATTERY: One (1) 3 Volt CR123A lithium battery, with a storage life of 10 years.

FEATURES: Ultra lightweight and compact.
High power LED for extreme brightness.
Ambidextrous operation.
One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching.
Securely fits on GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X Rail and GLOCK® 48 Rail using the provided key and jaw set.
Extensively live-fire tested.
Operating temperature: -40°F to +120°F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Serialized for positive identification.

APPROVALS:  Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited lifetime warranty.

OPTIONAL ACCESSORIES: N/A