



Highly visible, integrated 510-530nm green laser for accurate aiming

**Material/Lens** 6000 Series machined aircraft aluminum with black anodized finish. High-impact, chemical resistant engineering polymer laser housing. High temperature, shock-mounted, impact-resistant BOROFLOAT® glass lens; gasket sealed.

**Dims/Weight** Length: 3.39 in (8.61 cm); Width: 1.47 in (3.73 cm); Height: 1.83 in (4.64 cm); Weight: 4.72 oz (133.8 g) with batteries.

**Light Source/ Output** White LED technology, impervious to shock with a 50,000-hour lifetime. TIR optic produces a concentrated beam with optimum peripheral illumination. 300 lumens; 12,000 candela peak beam intensity; runs 1.5 hours (LED, laser/LED combo); 17 hours (laser only)

**Switch** Ambidextrous momentary/steady on-off switch.

**Battery** Uses two (2) CR123A lithium batteries (included).

**Features**

- One-handed snap-on/tighten interface keeps hands away from muzzle when attaching/detaching
- Mounts directly to handguns with GLOCK-style rails and to all MIL-STD-1913 (Picatinny) rails
- Includes keys for GLOCK Gen 4/5 style, Picatinny, Beretta 90two, S&W 99, S&W TSW, and SIG SAUER P320 XCarry frame models
- IPX4 water-resistant

**Approvals** Meets applicable United Kingdom and European Community Directives.

**Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse, and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
TLR-2 G – Includes Rail Locating Keys for GLOCK Gen 4/5 style, Picatinny, Beretta 90two, S&W 99, S&W TSW, and SIG SAUER P320 XCarry frame models, lithium batteries	080926-69250-3	69250

	Description	UPC	Item #
	TLR M-LOK® Mount	080926-88301-7	88301
	Vertical Grip with Rail - Machined aluminum, hard anodized ambidextrous rail grabber vertical foregrip with integral Picatinny rail and storage compartment	080926-69114-8	69114
	Flip Lens - Red	080926-69115-5	69115
	Flip Lens - Blue	080926-69116-2	69116
	Flip Lens - Green	080926-69117-9	69117
	Flip Lens - IR	080926-69118-6	69118
	Flip Lens - Opaque	080926-69124-7	69124
	Contour Remote - GLOCK® Gen 4/Gen 5 models with rails	080926-69300-5	69300
	Contour Remote - M&P	080926-69310-4	69310
	Contour Remote - SIG SAUER® P320® XCarry frame models	080926-69481-1	69481
	TLR Remote Door/Switch Assy (TLR-1/TLR-2 Series)	080926-69130-2	69130
	TLR Remote Door/Switch Assy with "Safe Off" (TLR-1 Series/TLR-2 Series)	080926-69161-2	69161
	Remote Pressure Switch Plug Coil (TLR-1/TLR-2 Series) shotgun coil remote switch allows for expansion of cord with pump action	080926-69134-6	69134
	Straight Momentary Pressure Switch (TLR-1/TLR-2 Series) long gun remote switch attaches to rail forend with included clips	080926-69135-3	69135
	Remote Tape Switch Plug, Straight (TLR-1/TLR-2 Series) Straight Remote tape switch fits most right-angle grips & other aftermarket accessories	080926-69132-2	69132
	Straight Latching Pressure Switch	080926-89008-4	89008
	TLR Dual Remote Switch	080926-69138-4	69138
	TLR-1/TLR-2 Series TLR Key Kit - Includes rail locating keys for GLOCK Gen 4/Gen 5 models with rails, 1913 Picatinny, S&W 99/TSW, Beretta 90two, and SIG SAUER P320 XCarry frame models and mounting tools	080926-69175-9	69175
	12 ga. Mag Tube Mount	080926-69901-4	69901
	REM 870 Rail	080926-69906-9	69906
	CR123A Lithium Batteries (2) Pack	080926-85175-7	85175
	CR123A Lithium Batteries (6) Pack	080926-85180-1	85150
	CR123A Lithium Batteries (12) Pack	080926-85177-1	85177
	CR123A Lithium Batteries (400) Pack	080926-85179-5	85179